

Dynamo Polyurethane Systems - Dynamo 100, CG 100 Series Resin Component B - Part B



SECTION 1 : IDENTIFICATION

1.1. Identification

Product form : Mixtures

Chemical Name : Polyurethane Resin B - Side

Product Type : Liquid

Identified Use : Component B of Spray - Applied System

Cas No. : Mixture

Product name : Dynamo D100, Dynamo D1000, CG 100, and CG 1000

1.2. Recommended use and restrictions on use

Use of the substance/mixture : A component for the production of high pressure spray foam

insulation

1.3. Supplier

Dynamo Polyurethane Systems Inc.

2113 Harwood Rd.

Ste 309 #900

Bedford, TX 76021

Tel: 469-799-9991

info@Dynamosps.com

1.4. Emergency telephone number

Emergency number : CHEMTREC (24 hours) 800-424-9300

International (24 hours) +1-703-527-3887

SECTION 2 : HAZARD(s) IDENTIFICATION

2.1. Classification of the substance or mixture

GHS-US classification

Acute toxicity (oral), Category 4 H302 Harmful if swallowed

Skin corrosion/irritation, Category 1B H314 Causes severe skin burns and eye damage

Serious eye damage/eye irritation, Category 1 H318 Causes serious eye damage

Full text of H statements: see section 16

SDS-US-Resin100-2025v_01DPSI

Dynamo Polyurethane Systems LLC •2113 Harwood Rd. • Ste 309 #900 • Bedford, Texas 76021 • 1-469-799-9991 • www.Dynamosps.com



Dynamo Polyurethane Systems - Dynamo 100, CG 100 Series Resin Component B - Part B



GHS LABEL ELEMENTS

GHS-US labelling

Hazard pictograms (GHS-US):





GHS05

Signal word (GHS-US) Danger

Hazard statements (GHS-US) H302: Harmful if swallowed.

H314: Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

Precautionary statements (GHS-US) : P260 - Do not breathe fume, mist, spray, vapors

P264 - Wash hands thoroughly after handling

P270 - Do not eat, drink or smoke when using this product

P280 - Wear respiratory protection, protective clothing, protective

gloves, eye protection

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce

vomiting

P303+P361+P353 - If on skin (or hair): Take off immediately all

contaminated clothing. Rinse skin with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep

comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing

P310 - Immediately call a doctor, a POISON CENTER

P330 - Rinse mouth

P363 - Wash contaminated clothing before reuse

P405 - Store locked up

P501 - Dispose of contents/container to comply with applicable

local, national and international regulation.

Other hazards which do not result in classification

No additional information available

SDS-US-Resin100-2025v_01DPSI

Dynamo Polyurethane Systems LLC • 2113 Harwood Rd. • Ste 309 #900 • Bedford, Texas 76021 • 1-469-799-9991 • www.Dynamosps.com



Dynamo Polyurethane Systems - Dynamo 100, CG 100 Series Resin Component B - Part B



2.4. Unknown acute toxicity (GHS US)
Not applicable

Not applicable

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient Name	Cas#	Concentration	Exposure	LimitsLD50/LC50
Dimethylamino- ethoxeyethanol	108-01-0	1%-5%	Not available	2337mg/kg (rat-oral)/ 1000mg/l 4hr (rat inhalation)
1,3-Propane diamine N'- (3-(dimethylamino- propyl)- N,N-dimethyl	6711-48-4	1%-5%	Not available	> 1.25g/kg (rat-oral)/ Not determined
Saction 1 ·	EIRST AID M	FACIIRES		

Section 4 : FIRST AID MEASURES

Eye contact : Rinse immediately with plenty of water for 15 minutes. Contact lenses should be re

moved. Immediately get medical attention.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. In

case of breathing difficulties administer oxygen. In case of irregular breathing or respiratory arrest provide artificial respiration. Get medical advice/attention if you feel un

well.

Skin contact: Remove contaminated clothing immediately. Wash skin thoroughly with mild soap and

water. Seek medical attention immediately.

Ingestion : Rinse mouth immediately and drink plenty of water. Induce vomiting. Never give any

thing by mouth to an unconscious person. If unconscious, place in the recovery posi-

tion and seek medical advice. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

After inhalation : May be harmful if inhaled. Prolonged exposure to liquid may cause a mild irritation.

After skin contact : Causes severe skin burns.
After eye contact : Causes serious eye damage.

SDS-US-Resin100-2025v_01DPSI

Dynamo Polyurethane Systems LLC • 2113 Harwood Rd. • Ste 309 #900 • Bedford, Texas 76021 • 1-469-799-9991 • www.Dynamosps.com



Dynamo Polyurethane Systems - Dynamo 100, CG 100 Series Resin Component B - Part B



After ingestion: Harmful if swallowed. May cause stomach pain or discomfort and gastrointestinal

disturbance.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Notes to Physician : Treat symptomatically.

Protection of first aiders : No action shall be taken involving any personal risk or without suitable

training. Use personal protective equipment. Avoid contact with skin,

eyes and clothing.

SECTION 5 : FIRE FIGHTING MEASURES

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Water. Dry extinguishing powder. Carbon dioxide. Alchol resistant foam.

Unsuitable extinguishing media: None known.

5.2. Specific hazards arising from the chemical

Fire hazard : Minimal fire hazard. Combustion may produce irritating fumes and carbon

oxides.

Explosion hazard : None known.

Specific hazards

arising from the

chemical

Carbon dioxide, carbon monoxide, oxides of nitrogen, dense black smoke.

Burning produces irritant fumes.

Reactivity : Stable under normal conditions of use.

5.3. Special protective equipment and precautions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk without suitable training. Fire fighters should wear appropriate protective equipment and self contained breathing apparatus with a full face piece operated in positive pressure mode. Move undamaged containers from immediate hazard area if it can be done safely.

Other information : Prevent entry to sewers and public waters.

SDS-US-Resin100-2025v_01DPSI



Dynamo Polyurethane Systems - Dynamo 100, CG 100 Series Resin Component B - Part B



SECTION 6 : Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. Spill Procedure : Clean up personnel must wear protective equipment to prevent contact

with the product. Evacuate the area of all unnecessary personnel. Stop spill at source. Use inert absorbent material such as sand, clay, earth or

floor absorbent to clean up spill. Shovel into drums.

6.1.2. Personal Precautions, :

protective equipment

and emergency procedures

Ensure adequate ventilation. Wear personal

protection equipment. Remove persons to safety. Do not breathe vapors

or spray mist.

6.2 Methods and material for :

containment and

cleaning up

Suitable material for taking up: Absorb spill with inert material (e.g. dry

sand or earth), then place in a chemical waste container.

Wash with plenty of water.

6.3 Environmental precautions: Prevent entry to sewers and public waters.

SECTION 7 : Handling and storage

7.1. Precautions for safe handling : Avoid mixing with air or use for any purpose above atmospheric

pressure. If possible use nitrogen (under pressure) to carry out transfers. No special fire protection measures are necessary.

7.2. Hygiene measures : Wash contaminated clothing prior to re-use. Always wash hands

and face immediately after handling this product, and once again before leaving the workplace. Do not eat, drink or smoke when using this product. Handle in accordance with good

industrial hygiene and safety practice.

7.3. Conditions for safe storage : Store product in accordance with local regulation. Store product

at room temperature away from heat and moisture. Store product in original container in a dry, cool, and well ventilated

area with local exhaust. Protect from freezing.

7.4. Incompatible materials : Strong oxidizing agents. Strong acid. Strong bases.

7.5. Storage temperature : $50 - 90^{\circ}F (10 - 32^{\circ}C)$

SECTION 8 : Exposure controls/personal protection

SDS-US-Resin100-2025v_01DPSI Page 5 of 12



Dynamo Polyurethane Systems - Dynamo 100, CG 100 Series Resin Component B - Part B



8.1. Appropriate engineering controls

Use ventilation adequate to keep exposures (airborne levels of controls dust, fume, vapor, etc) below recommended exposure limits. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes, and clothing. Do not breathe dust/fume/gas/mist/vapors.

8.3. Individual protection

Measures Eye Protection

When directly handling liquid product, eye protection is required, such as chemical safety goggles or chemical safety goggles in combination with a full-face shield when there is a greater risk of splash.

8.4. Hand protection

Impervious gloves e.g. PVC, nitrile rubber, butyl rubber

8.5 Skin and body protection

Long sleeved protective clothing. Chemical resistant apron

8.6. Respiratory protection

Spraying increases the risk of hazardous exposure. In atmospheres where the material is sprayed, workers should avoid contact with aerosols through proper engineering controls such as exhaust ventilation and proper protective equipment such as a full face air supplied respirators. NIOSH/MSHA approved air purifying respirator should be used if operating conditions produce airborne concentrations that exceed exposure limits for any individual components.

8.7. Hygiene Measures

Wash hands, forearms and face thoroughly after handling chemical products.

8.8. Personal Protective Equipment(PPE)

Protective goggles. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection.









SECTION 9 : Physical and chemical properties

9.1. Physical and chemical properties

Color : Milky white / Brown
Odor : Light ammonia
Odor Threshold (ppm) : Not available.

pH (Value) : ~11.0

SDS-US-Resin100-2025v_01DPSI

Dynamo Polyurethane Systems LLC •2113 Harwood Rd. • Ste 309 #900 • Bedford, Texas 76021 • 1-469-799-9991 • www.Dynamosps.com



Dynamo Polyurethane Systems - Dynamo 100, CG 100 Series Resin Component B - Part B



Melting Point (°C) /

Freezing Point (°C) 0 °C/32 °F Initial boiling point 212 °C/413 °F Flash Point (°C) Not applicable **Evaporation Rate** Not available Flammability (solid, gas) Not applicable Explosive Limit Ranges Not available Vapour pressure (Pascal) Not available Vapour Density (Air=1) Not available Density (g/ml) Not available

Specific Gravity @ 77°F (25°C): Summer formula – 1.15 g/cm³ / .415 lb/in³

Volatility : Not available

Viscosity : 500-100cps @ 20 °C/68 °F

Oxidizing properties : No data available

9.2. Other information

No additional information available

SECTION 10 : Stability and reactivity

10.1. Reactivity : Stable under normal conditions of use.

10.2. Chemical stability : Stable under normal conditions of use.

10.3. Possibility of : Not available

Hazardous Reactions

10.4. Incomparability : Reacts with strong oxidizing agents. Strong acids. Strong bases.

(Materials to avoid)

10.5. Conditions to Avoid : High temperatures, open flames and sparks. Do not use in areas with

out adequate ventilation. Temperatures > 85 °F(29 °C). Protect from

moisture. Direct sunlight. Excessive heat. Freezing.

10.6. Hazardous Polymerization : Polymerization will occur in contact with isocyanates.

10.7. Hazardous decomposition : Combustion may produce irritating fumes and carbon oxides.

Oxides of nitrogen and carbon. Other potentially toxic fumes.

SDS-US-Resin100-2025v_01DPSI



Dynamo Polyurethane Systems - Dynamo 100, CG 100 Series Resin Component B - Part B



SECTION 11 : Toxicological information

11.1. Information on toxicological effects

11.1.1 Exposure routes: Inhalation, Skin Contact, Eye Contact

11.1.2 Acute Toxcity

11.1.2 Nedec Toxerty .									
		Ingredient Name			LC50	LD50	LD50		
		,3 Propanediamine, N dimethylamino)prop N,Ndimethyl-	,		Not available	1620ug/kg oral, rat	Not available		
		Dimethylaminoethan	nol 2-		6.1mg/L 4 hours, (inhalation, rat)	1803mg/kg Oral, rat	Not available		
	11.2.	Irritation	:	Skin Irritation: Causes severe skin burns. Eye Irritant: Causes serious eye damage. Skin Sensitization: Not expected to be a skin or respiratory sensitizer.					
	11.3.	Sensitization	:						
	11.4.	Repeated dose toxicity	:	No information available					
	11.5	Carcinogenicity	:	No ingredients are listed as carcinogens by ACGIH and IRAC.					
	11.6	Mutagenicity	:	No info	ormation available				

SECTION 12 : Ecological information

12.1. Ecotoxicity : Not available.

12.2. Persistence and Degradability: Not expected to be rapidly biodegradable.

12.3 Mobility in Soil : Not available

12.4 Bioaccumulative Potential : Not available.

Other adverse effects: Not available

SDS-US-Resin100-2025v_01DPSI Page 8 of 12



Dynamo Polyurethane Systems - Dynamo 100, CG 100 Series Resin Component B - Part B



SECTION 13 : Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of this material and its container to hazardous or special

waste collection point.

Product/Packaging disposal : Comply with Federal, provincial, and local regulations on report-

recommendations ing releases. Consult your local or regional authorities.

Ecology - waste materials : Avoid release to the environment.

SECTION 14 : Transport information

Department of Transportation (DOT):

In accordance with DOT

Not regulated

Transportation of Dangerous Goods

Not regulated

Air transport

Not regulated

Transport by sea

Not regulated

SECTION 15 : Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture is not known to contain a toxic chemical (s) in excess of the applicable inconsquential concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

15.2. SARA 302 Extremly Hazardous Substances: NONE

15.3. Chemicals subject to SARA Reporting: NONE

SDS-US-Resin100-2025v_01DPSI Page 9 of 12



Dynamo Polyurethane Systems - Dynamo 100, CG 100 Series Resin Component B - Part B



This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

SECTION 16: Other information

16.1. Other information : The attention of the user is drawn to the risks possibly incurred by using

the product for any other purpose than that for which it was intended

16.2. H-statement(s) : H302 Harmful if swallowed

H312 Harmful in contact with skin

H314 Causes severe skin burns and eye damage

H315 Causes skin irritation

H318 Causes serious eye damageH319 Causes serious eye irritation

H331 Toxic if inhaled H332 Harmful if inhaled

16.3. Safety Data Sheet

issued by Product Safety Department This information is furnished without warranty, expressed or implied,

except that it is accurate to the best knowledge of Dynamo

Polyurethane Systems Inc.

Dynamo Polyurethane Systems LLC assumes no legal responsibility for

use or reliance upon this data. It is the user's responsibility to ensure

that their activities comply with federal, state, or local laws.

Date of Issue : January 2025

Additional Information : NONE